

ABD

Automatic Balancing Damper



- Ultra Compact design - 6" high.
- No exhaust collar required
- Used on multiple hoods with common exhaust.
- Does not accumulate grease like guillotine type dampers.
- Actuator access from below.
- Actuator fail safe opens on power interruption.

Specification

Furnish and install a Model ABD automatic kitchen exhaust balancing damper as manufactured by Halton. The balancing damper shall bear the ETL label per, ETL listed to Standard for Exhaust hoods for Commercial Cooking Equipment UL 710, Standard for Exhaust Hood and Related Controls for Commercial and Institutional Kitchen ULC-S646-06 and be fabricated in compliance with NFPA-96.

The installation shall be in accordance with the manufacturer's recommendations and conform to NFPA-96 guidelines and all applicable local codes. The size shall be as indicated on drawings and/or equipment schedule and match the exhaust collar size for the hood system.



The damper shall automatically adjust exhaust airflow based on direct pressure readings from integral T.A.B. test and balance port in the Capture Jet hood. The Model ABD will have night time setback feature which will automatically close the damper when the exhaust system is shut down to prevent outside air from migrating into the space. The Model ABD will fail safe open on power interruption.

The damper outer casing shall be constructed of continuously welded 16 ga. aluminized steel including the balancing blades. Optional construction is of 16 ga. stainless steel. Adjustment of the parallel dampers (in open position) will be achieved by an electric motor turning the adjustment bracket until the desired pressure reading is achieved. Access to the actuator motor will be from underneath.


Damper is provided with fire suppression piping and nozzle for duct protection above the balancing damper blades. Damper includes Grease Deposition Sensors (KGS) and Temperature sensor to work in conjunction with Thermal Imaging Sensors and Halton SafeGuard system.

Model ABD is to be used on Capture Jet style hoods, models KVE, KVC, KVL, KVM, KVV, KVR and KVO.

DIMENSIONS



ACTUATOR: BELIMO



NOTE: Outer construction of damper must match the unexposed construction of the corresponding hood. Inner construction of the damper must match the exposed construction of corresponding hood.

The company has a policy of continuous product development, therefore we reserve the right to modify design and specifications without notice.

For more information, please contact your nearest Halton agency. To find it: www.halton.com