

HDWCK+1 – Double wall reduced wall clearance grease duct (UL)



Features & Benefits

- Only 1/16 inch per foot slope is required
- Factory CAD designs for installation ease
- All lengths are field-cutttable for maximum flexibility
- 100% stainless steel with Limited Lifetime Warranty
- Smooth flow and known resistance for perfected factory pressure calculations

Specification

Connection / Installation Details

2.2" overlapping joint with Patent-Pending lightweight technology and a double female socket permitting fastest alignment/installation on the market:

1. Use supplied silicone sealant to make the complete seal
2. Push the male/female ends together
3. Install the locking band to assure correct engagement

Materials

- Made of all stainless steel (both inner and outer jacket), thickness per UL-1978 Listing
- 1.5" thick ceramic fiber insulation compressed into a 1.25" thick space
- All supports and accessories are stainless steel

Diameters:

6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, & 36 (use DWFL+1 for diameters 38" through 48")

Available Lengths:

9", 12", 18", 24", 30", 36", 42", & 48" (or any fixed length between)

Available Fittings:

Any elbow or tee, over 80 catalog fittings per each diameter

Available Accessories:

All-stainless supports, guides, hangers, adapters – over 25 accessories per each diameter